

G-8016

Apex-i

Features

- User-friendly GUI for easy operation
- Connection to IP camera, IP dome and video server
- Connection to Hikvision, Panasonic, Sony, AXIS, Bosch, SANYO IP cameras, etc
- Support decoding at H.264, MPEG4 compression standard, etc.
- Stream storage at PS standard capsulation format
- Up to 1280×1024 VGA output resolution
- Support high-definition video preview, storage and playback.
- Digital zoom in preview and playback
- Up to 16-ch synchronous playback
- Smart search and playback for recorded video with moving object
- Different recording storage period configurable for each channel
- Redundant recording
- HDD management in groups
- NTP, SADP, SMTP and NFS protocols supported



Specifications

Model	G-8016		
Video/Audio input	Video compression	H.264	
	Analog Video input	16-ch, BNC(1.0Vp-p, 75Ω), PAL/NTSC adaptive	
	IP Video input	16-ch 4CIF or 8-ch HD IP Camera/speed dome/DVS	
	Composited video input	24-ch (Analog video + IP video)	
	Audio compression	OggVorbis	
	Audio input	16-ch, BNC(2Vp-p, 1kΩ)	
Voice talk input		2, BNC(2Vp-p, 1kΩ)	
Video/Audio output	Preview resolution	PAL:704×576 NTSC:704×480	
	VGA output	1, resolution: 1024×768/60Hz, 1024×768/70Hz, 1280×1024/60Hz	
	Encoding resolution	UXGA/720P/4CIF/DCIF/2CIF/CIF/QCIF	
	Video output	2-ch, BNC(1.0Vp-p, 75Ω)	
	Video loop out	optional	
	Frame rate	UXGA/720P/4CIF/DCIF/2CIF/CIF:25fps(P)/30fps(N)	
	Video bit rate	32Kbps~2048Kbps, or user-defined (Max. 6144Kbps)	
	Audio output	2-ch, BNC(Linear Electrical Level, 600Ω)	
	Audio bit rate	16kbps	
	Dual Stream	Support	
	Stream Type	Video/Video & Audio	
	Synchronous playback	16-ch	
	Hard disk	Type	8 SATA interface
		Capacity	Each interface supports more than 2TB capacity
External interface	Network interface	1, RJ45 10M/100M/1000M adaptive Ethernet interface	
	Serial interface	1 RS-232 interface (for parameters configuration, maintenance , transparent channel); 1 RS-485 interface (for PTZ control); 1 RS-485 keyboard interface (for special keyboard control)	
Others	USB interface	3, USB2.0	
	Alarm in	16	
	Alarm out	4	
	Power supply	100~240VAC, 6.3A, 50~60Hz	
	Consumption	≤70W (without hard disk or DVD-R/W)	
	Working temperature	-10°C~+55°C	
	Working humidity	10%~90%	
	Size	450mm(D)×450mm(W)×95mm(H)	
	Weight	≤8Kg (without hard disk or DVD-R/W)	

販売代理店 ディスクテック(株) 電話 053-450-3781 sales@disctech.co.jp

Apex-I International CO., LTD
6F No.5-1, Innovation 1st RD Science-Based industrial Park Hsinchu 30076, Taiwan, R.O.C
TEL : +886-3-668-7070 FAX : +886-3-668-7171